



The Model T200U Trace-Level Chemiluminescence NO/NO₂/NO_x Analyzer



The Model T200U analyzer achieves low level NO / NO₂ / NO_x measurements using the proven Chemiluminescence principle and advanced electronics. The T200U combines high sensitivity with a wide dynamic measurement range making it ideal for ambient air quality, and other low-level applications.

— Available with NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty

T200U Specifications

■ Ranges	Min: 0 - 5 ppb full scale Max: 0 - 2,000 ppb full scale (selectable, independent NO, NO ₂ , NO _x ranges)
■ Measurement Units	ppb, µg/m ³ (selectable)
■ Zero Noise	< 25 ppt (RMS)
■ Span Noise	< 0.5% of reading (RMS) above 5 ppb
■ Lower Detectable Limit	50 ppt
■ Zero Drift	< 0.1 ppb/24 hours
■ Span Drift	< 0.5% of reading/24 hours
■ Lag Time	20 seconds
■ Rise/Fall Time	< 50 seconds to 95%
■ Linearity	1% of full scale
■ Precision	0.5% of reading above 5 ppb
■ Sample Flow Rate	1,000 cc/min ±10%
■ Power Requirements	100V-120V, 220V-240V, 50/60 Hz
■ Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
■ Recorder Offset	±10%
■ Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
■ Optional I/O	1 x USB com port 1 x RS485 8 x analog inputs (0-10V, 12-bit) 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
■ Operating Temperature Range	5 - 40°C 20 - 30°C (with US EPA Equivalency)
■ Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
■ Weight	Analyzer: 40 lbs (18 kg) External pump: 21 lbs (9.5 kg)
■ Certifications*	US EPA: RFNA-1194-099

* All certifications apply for legacy or NumaView™ T Series analyzer software

NumaView™ software is available as a no-charge option that must be specified at the time of purchase.

Specifications subject to change without notice.
All specifications are based on constant conditions.



TELEDYNE
ADVANCED POLLUTION INSTRUMENTATION
Everywhere you look™

9970 Carroll Canyon Road ■ San Diego, CA 92131
Ph. 858-657-9800 Fax 858-657-9816
Email api-sales@teledyne.com

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2016 Teledyne Advanced Pollution Instrumentation
Printed documents are uncontrolled. SAL000049D
(DCN 7304) 07.18.16

